



Capitol Type S Masonry Cement

Product Name: Capitol Type S Masonry Cement

Manufacturing Location:

Capitol Aggregates, Inc.
11511 Nacogdoches Road
San Antonio, TX 78217

Description: Capitol Type S High Bond Masonry Cement Meets the requirements of ASTM C91-05 *Standard Specification for Masonry Cement* as a Type S cement. Capitol Type S can be used in as cement in masonry and plastering construction. The primary use for Capitol type S is in preparation of *Specification C 270 Type S* mortar without further addition of cements or hydrated lime.

Packaging: Bulk and 75 (34 kg.) Bags

Technical Data

ASTM International

- ASTM C 91 *Standard Specification for Masonry Cement*
- ASTM C 270 *Standard Specification for Mortar or Unit Masonry*
- ASTM C 387 *Standard Specification for Packaged, Dry, Combined Materials for Mortar and Concrete*
- ASTM C 1157 *Standard Performance Specification for Hydraulic Cements*

Consult the following documents for general guidance on using Capitol Type S in mortar for masonry applications

American Concrete Institute (ACI)

- ACI 530.1 *Specification for Masonry Structures*
- ACI 225R-99 *Guide to the Selection and Use of Hydraulic Cements*

Application

- Capitol Type S can be mixed with masonry sand to produce a mortar suitable for brick, block, or stone as used in chimneys and walls or in stucco applications.

Suggested Proportions for Mortar

- 2 1/4 to 3 parts mason sand(13-18 Shovels)
- 1 part masonry cement
- Add water to achieve desired consistency
-

Mix for 5-7 minutes.

Safety

REFER TO THE MATERIAL DATA SAFETY SHEET (MSDS) BEFORE USING THIS PRODUCT. COPIES OF THE MSDS ARE AVAILABLE BY CONTACTING CAPITIL AGGREGATES. PHONE 1-210-871-6100 OR BY EMAIL; info@capitolaggregates.com

Technical Support

For technical assistance please contact Capitol Aggregates by phone; 210-871-6119 or via email; info@capitolaggregates.com